

## MODULE SPECIFICATIONS



# ELEMENT SERIES

## CASTVision™

### EXTERIOR LED PRODUCTS

PRODUCT NAME	eCV217S-2.5
PIXEL PITCH	2.5 mm
LED TYPE	SMD
BRIGHTNESS	3500 Nits
ASPECT RATIO	16:9
RESOLUTION / MODULE	1920 x 1080 Pixels
TOTAL PIXELS	2,073,600 Pixels
REFRESH RATE	3840 Hz
FRAMES PER SECOND	60 FPS / 120 FPS
COLOR DEPTH (BITS/ CHANNEL)	16
COLORS	281.5 Trillion
COLOR TEMPERATURE	2,000K - 10,000K
CONTRAST RATIO	4000:1
POWER	110-240 VAC, 50/60 Hz
MAX. POWER @100% FULL WHITE	9331 Watts
TYPICAL POWER CONSUMPTION*	2799 Watts
ANTICIPATED LIFETIME	100,000 Hours
DIMMING CAPABILITY	1-100%, in 1% Increments
VIEWING ANGLE HORIZONTAL	160°
VIEWING ANGLE VERTICAL	160°
HEIGHT	106.3" (2700mm)
WIDTH	189" (4800mm)
DEPTH	7.1" (180mm)
SERVICE ACCESS	Front Access
WEIGHT / MODULE	1433 Lbs(650 kg)
OPERATING TEMPERATURE	-4° to 122°F (-20° to 50°C )
STORAGE TEMPERATURE	-22° to 140°F (-30° to 60°C )
CERTIFICATION	EMC, ETL, CE, RoHS, FCC class A
ENVIRONMENTAL RATING	IP65/IP54 (Front/ Back)

Technical specifications are for reference and subject to change without prior notice. Please contact i5LED for further information. LED Type, Brightness, Refresh Rate, Color-Depth and various other specifications may be configured specifically to project requirements.

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense. (FCC 47 CFR § 15.105)