

MODULE SPECIFICATIONS



ICON SERIES

INTERIOR LED PRODUCTS

CASTVision™ FD

PRODUCT NAME	CastVision FD
PIXEL PITCH	1.5 mm
BRIGHTNESS	600 Nits
ASPECT RATIO	16:9
RESOLUTION / MODULE	1920 x 1080 Pixels
TOTAL PIXELS	2,073,600 Pixels
REFRESH RATE	3840 Hz
FRAMES PER SECOND	60 FPS / 120 FPS
COLOR TEMPERATURE	2,000K - 10,000K
CONTRAST RATIO	6000 : 1
MAX. POWER @100% FULL WHITE	2100 Watts
TYPICAL POWER CONSUMPTION*	630 Watts
ANTICIPATED LIFETIME	100,000 Hours
DIMMING CAPABILITY	Yes
VIEWING ANGLE HORIZONTAL	160°
VIEWING ANGLE VERTICAL	160°
VIEWING AREA	118 in x 66.44 in (135" Diagonal)
HEIGHT	103 in
WIDTH	118.5 in
DEPTH	30 in
SERVICE ACCESS	Front Access
WEIGHT	255 kg
CERTIFICATION	3C CE ETL FCC
ENVIRONMENTAL RATING	IP66

Technical specifications are for reference and subject to change without prior notice. Please contact i5LED for further information. LED Type, Brightness, Refresh Rate, Color-Depth and various other specifications may be configured specifically to project requirements.

*Under controlled testing parameters, please note this is not an outdoor-rated product.

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense. (FCC 47 CFR § 15.105)