

i5LED™



ELEMENT

## STREET View™

FINE-PITCH OUTDOOR  
LED KIOSK — SINGLE  
OR DOUBLE-SIDED



The i5LED, StreetView™ is a fine-pitch, high-brightness outdoor LED kiosk designed to deliver vibrant, high-resolution content in public spaces—day or night, rain or shine.

Designed for 24/7 operation, it features fine-pitch LED for superior visuals, intelligent content control, and durable, all-weather construction in a compact, modern form.

Available in three sizes and configurable as single- or double-sided, StreetView™ adapts to a wide range of environments—from pedestrian zones to transit platforms.

R0.0

[sales@i5LED.com](mailto:sales@i5LED.com)

1.844.464.5533



**PROTECTIVE GLASS:**

4+4 Tempered laminated glass, anti-reflection (AR) coating

WEATHERPROOF STRUCTURE



**SIZES:** 57" / 79" / 101" (single or double-sided)

**PIXEL PITCHES:** 1.25mm / 1.56mm / 1.95mm

**PROTECTIVE GLASS:** 4+4 tempered laminated with anti-reflection (AR) coating

**DIRECTVIEW LED:** Ultra-thin, LED modules with Advanced Polymer Protection

**CONTROL:** BrightSign® player with Ethernet, optional Wi-Fi, USB-C, and touchscreen support

**POWER MANAGEMENT:** 8 relays, remote scheduling

**SMART SENSORS:** Ambient light, temperature, humidity

**APPLICATIONS:** Retail, airports, EV charging, smart cities, malls, campuses, transit & more

TECHNICAL SPECIFICATIONS

PRODUCT NAME	57"		79"			101"		
	SV-1.2-SMD-57	SV-1.5-SMD-57	SV-1.2-SMD-79	SV-1.5-SMD-79	SV-1.9-SMD-79	SV-1.2-SMD-101	SV-1.5-SMD-101	SV-1.9-SMD-101
PIXEL PITCH	1.25 mm	1.56 mm	1.25 mm	1.56 mm	1.95 mm	1.25 mm	1.56 mm	1.95 mm
DISPLAY ORIENTATION*	Portrait		Portrait			Portrait		
BRIGHTNESS	4,000 Nits		4,000 Nits			4,000 Nits		
DIAGONAL	750 x 1,250mm (57")		1,000 x 1,750mm (79")			1,250 x 2,250 (101")		
RESOLUTION (PIXELS)	600 x 1000	480 x 800	800 x 1,400	640 x 1,120	512 x 896	1,000 x 1,800	800 x 1,440	640 x 1,152
REFRESH RATE	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz	3,840 Hz
COLOR DEPTH	16 Bit	16 Bit	16 Bit	16 Bit	16 Bit	16 Bit	16 Bit	16 Bit
MAX POWER USE PER KIOSK SINGLE FACED	765 Watts	765 Watts	1,428 Watts	1,428 Watts	1,428 Watts	2,295 Watts	2,295 Watts	2,295 Watts
SERVICE	Front & Rear		Front & Rear			Front & Rear		
ENVIRONMENTAL RATING	IP65 Front & Rear		IP65 Front & Rear			IP65 Front & Rear		

\*Landscape orientation also available. Ask us for details.

For more product information, please visit: [i5led.com/StreetView/](https://i5led.com/StreetView/)

Technical specifications are for reference and subject to change without prior notice. Please contact i5LED for further information.

